

베이커리 전용 냉동고는 소프트밀의 모든 기술력이 집약되어 첨단제상기능, 냉기내부순환 등 하이퀄리티 냉동고의 역할을 수행합니다.

## 급속냉동고 4도어(-35°C)

### -35°C 급속냉동

일본산부품과 명장 냉동기술을 적용하여 국내최고의 냉각성능을 발휘합니다. (초저온 스크롤 컴프레서 장착)



### 완벽한 냉기 차단

대형소프트밀만의 특수 가스켓을 적용해 밀폐력을 높이고 결로를 최소화 합니다.



## 급속냉동고 2도어

### LCD 컨트롤러

편리한 셋팅과 냉동보관 설정 등의 각종기능을 손쉽게 할 수 있습니다. (\*\*-35°C / \*-20°C)



### 강력한 대류냉각 시스템

대류팬 모터가 냉동고 내부 깊숙이 냉기를 순환시켜 안정적인 생산을 할 수 있습니다.



### 냉기순환식 내부구조

급속 냉기가 제품에 직접 닿지 않는 특화된 냉기순환식 내부구조로 설계되어 마르지 않고 제품 고유의 수분을 지켜 줍니다.

### 특수 경첩 적용

특수 경첩을 적용하여 밀폐력을 높이고, 분리가 가능하여 위생적으로 사용할 수 있습니다.



### 소프트밀 급냉시스템(SQC:Softmill Quick Composition)

• 급속냉동고와 냉동고를 같이 구성하여 급속냉동후의 보관까지 생각합니다.



▶ 급속냉동 · 냉동보관 ◀



▶ 급속냉동 · 냉동보관 ◀

| 모 델   | SDHQ-28                                   | SDHQ-18                   |
|-------|---|---------------------------|
| 규 격   | 1110(W) x 900(D) x 2030(H)                | 900(W) x 860(D) x 2030(H) |
| 용 량   | 28매                                       | 18매                       |
| 소비전력  | 380V, 3P, 3.5kW                           | 380V, 3P, 3.5kW           |
| 설 치 시 | 배수관 (50A) 필요. 밀폐된 공간에 설치시 협의 필요. 배기 시설 필요 |                           |



*This freezer is exclusively used for bakery, it is produced with all the technologies of SOFTMILL as a high-quality freezer with the functions of cutting-edge defrosting and cold air circulation.*

## Quick Freezer 4 doors (-35°C)

### -35°C Quick Freezing

It has the best cooling performance in Korea as Japanese-made parts and master cooling technologies are used.

(Equipped with a cryogenic scroll compressor)



### Perfect cold air blocking

As Daehung Softmill's special gaskets are used, it shows excellent airtightness, minimizing dew condensation.



## Quick Freezer 2 Doors

### LCD Controller

You can easily control various functions such as cold storage with convenient setting. (\*\*-35°C / \*-20°C)



### Powerful Convection Cooling System

As a convection fan motor circulates cold air inside the freezer, you can produce products stably.



### Cold Air Circulation Internal Structure

A specialized cold air circulation structure is designed to prevent the cold air from touching the products directly, thus keeping the moisture of the product without getting dry.

### Use of special hinges

The use of special hinges enhances airtightness and makes it possible to detach them for hygienic use.



### SOFTMILL Quick Cooling System (SQC: Softmill Quick Composition)

As a quick freezer and a freezer are combined together, you can store the products easily after quick cooling.



▶ Quick cooling - Cold storage ◀



▶ Quick cooling - Cold storage ◀

| Model                       | SDHQ-28  | SDHQ-18                   |
|-----------------------------|--|---------------------------|
| Dimension                   | 1110(W) x 1000(D) x 2030(H)  | 900(W) x 960(D) x 2030(H) |
| Capacity                    | 28 trays   | 18 trays                  |
| Power consumption           | 380V, 3P, 3.5kW  | 380V, 3P, 3.5kW           |
| At the time of installation | Drain pipe (50A) and exhaust facility are required. Consultation is required if it is installed in a sealed space. |                           |